

POSIFLEX

TM 3010E



TM 3010E

Display

LCD	9.7" TFT LCD
Resolution	Up to 1024 x 768
Active Area	196.61 [H] x 147.46 [V]
Pixel Pitch	0.192 [H] x 0.192 [V]
Pixel Arrangement	RGB Vertical Stripe
Viewing Angle	60/70/70/70 degree [U/D/L/R]
Contrast Ratio	500:01:00
Response Time	20 ms (Raising + Falling)
Brightness	350 cd/m ²

Touch

Touch Type	Bezel-free PCAP touch
Interface	USB

General Specification

Display Interface	VGA
Power Supply	12V from Posiflex terminal VGA port
Dimension (W x D x H in mm)	N/A
Weight (N.W. in kg)	N/A
Operating Condition	N/A

Support

System Supported	10" & 15" & 17" KS Series
------------------	---------------------------



Posiflex Technology (India) Pvt Ltd., India HQ

#985, 1ST A Main Road, 4th Cross, New Tippasandra, Bangalore 560 075

Tel : +91 80 40782700/20 | Mob: +91 953 543 2110

Email: sales@posiflexindia.com | www.posiflexindia.com

POSIFLEX TECHNOLOGY, INC. (Global HQ)

Add No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan

Authorized Distributor / Reseller