

# HC1621P/Pro

## Benefits:

- Industrial grade construction for maximum performance
- IP65 rated front panel with True-flat PCAP multi-touch
- Open standard interfaces enables easy to interface with ERP system for WIP, SPC and Inventory control
- Machine Control, Process Automation, Shop floor monitoring, control room and warehouse Management
- Supports various mount options: panel, desktop, and VESA arm

## Specification HC 1621P Pro

|                |   |
|----------------|---|
| Processor      | Intel Kaby Lake i7-7700T, up to 3.30 GHz, 6M Cache    |
| System Memory  | DDR4 SO-DIMM 32GB in 2 slots                          |
| Storage Device | SATA connector x 1 + M.2 connector [support AHCI] x 2 |
| Power Supply   | 12V/84W   |
| OS Support     | Windows 10 IoT 64 bit                                 |

## Display & Touch

|            |  |
|------------|--|
| LCD        | 21.5" TFT LCD  |
| Resolution | 1920 x 1080  |
| Touch      | True-flat PCAP touch with multi-touch support (IP65 on front panel); Optional AG glass |

## I/O Expansion

|                   |  |
|-------------------|--|
| Serial Port       | DB9 x 2                                      |
| OTG USB Port      | Micro-USB x 1                                |
| Standard USB Port | 4, USB 3.0 x 1 + USB 2.0 x 3                 |
| CR Port           | 1, control 2 x cash drawer, 24V support only |
| LAN Port          | 10/100/1000 Mb x 1                           |
| Display Port      | HDMI x 1                                     |
| Audio             | Internal 3W speaker x 2 + Mic-in/Line-out    |
| Expansion Slot    | Mini-PCIe for WiFi x 1                       |

## Physical Dimension

|           |                                  |
|-----------|----------------------------------|
| Dimension | 547 x 61 x 377 (W x D x H in mm) |
| Weight    | 6.6 kg                           |

## Environmental

|                     |                             |
|---------------------|-----------------------------|
| Operating Condition | 0°C - 50°C, 20%RH - 90%RH   |
| Storage Condition   | -20°C - 70°C, 10%RH - 90%RH |

\*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

\*The product information and specifications are subject to change without prior notice.

\*Please refer to the website for more attachment options.

## Certifications



VO.1\_13122022

**POSIFLEX**

**POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.,**  
#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavara, Bengaluru, Karnataka - 560093.  
Tel : +91 80 4078 2700 | Mob : +91 9535432110  
Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller

**POSIFLEX**



# HC1621P/Pro

21.5" Industrial Touch Terminal

