



2D Handheld
Barcode Scanner

CD-3301U

Form Factor	Handheld 2D Barcode Scanner
Light Source	White light LED
Resolution	640 x 480 pixels
Depth of Field	25-300mm @ EAN 13mil PCS=100% ; 30-350mm @ QR 20mil PCS=100%
Reading Skew Angle	-55 to 0°, 0 to +55°
Reading Pitch Angle	-55 to 0°, 0 to +55°
Min. PCS value	>25% QR code (30 mil)
Scan Method	CMOS array sensor
Scan Angle	Horizontal: 45°; Vertical: 34°
Decode Capability	<ul style="list-style-type: none"> • 1D: UPC/EAN/JAN,UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 &JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode), RSS-14、 RSS-Limited、 RSS-Expand, etc. • 2D: QR Code, Data Matrix, PDF417, Aztec, Maxicode, Dotcode, GS1 DataBar stack, etc.
Min. Resolution	≥4mil
Interface	USB
Dimension [W x D x H in mm]	66 x 94 x 173
Weight [N. W. in g]	143 (without cable)
Input Voltage	5.0 +/- 0.5V
Operating current	190mA
Operating temperature	-30°C to 60°C
Storage temperature	-40°C to 70°C
Ambient light	Direct Sun light: 0~100,000 lux max.
Drop resistance	150 cm

Options

Scanner stand (ST-3300BK-B)

VO.1_29022024